

[Sign in](#)

[Google](#)
[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)
[interactionSpec set property "resource adapter"](#) [Search](#) [Advanced Search](#) [Preferences](#)

WebResults 1 - 10 of about 458 for **interactionSpec set property "resource adapter"**. (0.50 seconds)[Sun ONE Connector Builder 2.0 Developer's Guide: Modifying the ...](#)

The **resource adapter** definitions can be modified by either launching the appropriate **Property Editor** directly from the contextual menu or by choosing ...
docs.sun.com/source/817-0540-10/Ch_04_mo.html - 41k - [Cached](#) - [Similar pages](#)

[Sun ONE Connector Builder 2.0 Developer's Guide: Creating the ...](#)

An **InteractionSpec** represents the way an EIS API method can be called ... Indicates **properties** whose values can be **set** at run-time by users of the adapter. ...
docs.sun.com/source/817-0540-10/Ch_03_cr.html - 55k - [Cached](#) - [Similar pages](#)
[\[More results from docs.sun.com \]](#)

[Setting InteractionSpec properties](#)

In the **InteractionSpec properties** for your Java method field, ... TPN Transaction under which you want all programs started by the **resource adapter** to run. ...
publib.boulder.ibm.com/.../radhelp/v6r0m1/
topic/com.ibm.etools.j2c.doc/topics/tsavingdatabaseanproperties.html - 7k - [Cached](#) - [Similar pages](#)

[Overview of the programming interface of the J2EE Connector ...](#)

As with the Connection, Interactions can have custom **properties** set by the CICS-specific **InteractionSpec** class (ECIInteractionSpec or EPPIInteractionSpec). ...
publib.boulder.ibm.com/infocenter/cicstg/
v6r1m0/topic/com.ibm.cics.tg.doc/cclao/cclaom0035.htm - 11k - [Cached](#) - [Similar pages](#)
[\[More results from publib.boulder.ibm.com \]](#)

[Common Client Interface](#)

InteractionSpec : Holds **properties** pertaining to an application ... the execute method: the **InteractionSpec** object with the correctly **set properties** for the ...
java.sun.com/j2ee/tutorial/1_3-fcs/doc/Connector5.html - 42k - [Cached](#) - [Similar pages](#)

[Using the J2EE Connector Architecture Common Client Interface](#)

Connection Represents a connection (using the **resource adapter**) to an EIS ... method: the **InteractionSpec** object with the correctly **set properties** for the ...
java.sun.com/developer/technicalArticles/J2EE/connectorclient/index.html - 51k - [Cached](#) - [Similar pages](#)

[BEA WebLogic Integration documentation: Package com.bea.adapter.cci](#)

The CCI specification defines a **set of standard properties** for an **InteractionSpec**. An **InteractionSpec** implementation is not required to support a standard ...
edocs.bea.com/wli/docs70/classdocs/com/bea/adapter/cci/package-summary.html - 39k - [Cached](#) - [Similar pages](#)

[WSDL J2C Extension](#)

The interaction **properties** to be **set** on an **InteractionSpec**. ... The element that a **Resource Adapter** must implement is the dynamic provider. ...
ws.apache.org/wsif/providers/wsdl_extensions/j2c_extension.html - 35k - [Cached](#) - [Similar pages](#)

[Object Computing, Inc. - Java News Brief - May 2002](#)

The JCA Common Client Interface (CCI) is a **set of interfaces** providing a framework for

basic interaction with a **Resource Adapter**. An adapter that supports ...
www.ociweb.com/jnb/jnbMay2002.html - 31k - [Cached](#) - [Similar pages](#)

Implementing Interaction Functions (SAP Library - Development Manual)

A **resource adapter** that implements the interaction-related interfaces from the ... The **InteractionSpec** is used to provide the **properties** for driving an ...
help.sap.com/saphelp_nw04/helpdata/en/e1/64861cdc574cb28ae4ea3cf95f60ca/content.htm - 17k - [Cached](#) - [Similar pages](#)

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [**Next**](#)

Get organized for the new year with [Google Desktop](#).

[interactionSpec set property "resour](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2007 Google

[Google](#)[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#) [Search](#) [Advanced Search](#)[Preferences](#)**Web**Results 1 - 10 of about 458 for **interactionSpec set property "resource adapter"**. (0.50 seconds)[Sun ONE Connector Builder 2.0 Developer's Guide: Modifying the ...](#)

The **resource adapter** definitions can be modified by either launching the appropriate **Property Editor** directly from the contextual menu or by choosing ...

docs.sun.com/source/817-0540-10/Ch_04_mo.html - 41k - [Cached](#) - [Similar pages](#)

[Sun ONE Connector Builder 2.0 Developer's Guide: Creating the ...](#)

An **InteractionSpec** represents the way an EIS API method can be called ... Indicates **properties** whose values can be **set** at run-time by users of the adapter. ...

docs.sun.com/source/817-0540-10/Ch_03_cr.html - 55k - [Cached](#) - [Similar pages](#)
[\[More results from docs.sun.com \]](#)

[Setting InteractionSpec properties](#)

In the **InteractionSpec properties** for your Java method field, ... TPN Transaction under which you want all programs started by the **resource adapter** to run. ...

publib.boulder.ibm.com/.../radhelp/v6r0m1/topic/com.ibm.etools.j2c.doc/topics/tsavingdatabaseanproperties.html - 7k - [Cached](#) - [Similar pages](#)

[Overview of the programming interface of the J2EE Connector ...](#)

As with the Connection, Interactions can have custom **properties set** by the CICS-specific **InteractionSpec** class (ECIInteractionSpec or EPIInteractionSpec). ...

publib.boulder.ibm.com/infocenter/cicstg/v6r1m0/topic/com.ibm.cics.tg.doc/cclao/cclaom0035.htm - 11k - [Cached](#) - [Similar pages](#)
[\[More results from publib.boulder.ibm.com \]](#)

[Common Client Interface](#)

InteractionSpec : Holds **properties** pertaining to an application ... the execute method: the **InteractionSpec** object with the correctly **set properties** for the ...

java.sun.com/j2ee/tutorial/1_3-fcs/doc/Connector5.html - 42k - [Cached](#) - [Similar pages](#)

[Using the J2EE Connector Architecture Common Client Interface](#)

Connection Represents a connection (using the **resource adapter**) to an EIS ... method: the **InteractionSpec** object with the correctly **set properties** for the ...

java.sun.com/developer/technicalArticles/J2EE/connectorclient/index.html - 51k - [Cached](#) - [Similar pages](#)

[BEA WebLogic Integration documentation: Package com.bea.adapter.cci](#)

The CCI specification defines a **set** of standard **properties** for an **InteractionSpec**. An **InteractionSpec** implementation is not required to support a standard ...
edocs.bea.com/wli/docs70/classdocs/com/bea/adapter/cci/package-summary.html - 39k - [Cached](#) - [Similar pages](#)

[WSDL J2C Extension](#)

The interaction **properties** to be **set** on an **InteractionSpec**. ... The element that a **Resource Adapter** must implement is the dynamic provider. ...

ws.apache.org/wsif/providers/wsdl_extensions/j2c_extension.html - 35k - [Cached](#) - [Similar pages](#)

[Object Computing, Inc. - Java News Brief - May 2002](#)

The JCA Common Client Interface (CCI) is a **set** of interfaces providing a framework for

[Sign in](#)

basic interaction with a **Resource Adapter**. An adapter that supports ...
www.ociweb.com/jnb/jnbMay2002.html - 31k - [Cached](#) - [Similar pages](#)

Implementing Interaction Functions (SAP Library - Development Manual)

A **resource adapter** that implements the interaction-related interfaces from the ... The **InteractionSpec** is used to provide the **properties** for driving an ...
help.sap.com/saphelp_nw04/helpdata/en/e1/64861cdc574cb28ae4ea3cf95f60ca/content.htm - 17k - [Cached](#) - [Similar pages](#)

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

Get organized for the new year with [Google Desktop](#).

[Search](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2007 Google

[Sign in](#)

[Google](#)

[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)

[Search](#) [Advanced Search](#)

[Preferences](#)

Web Results 1 - 10 of about 36 for "[java connector architecture](#)" interactionSpec connectionSpec set property "resource

[Object Computing, Inc. - Java News Brief - May 2002](#)

For example, **ConnectionSpec** utilizes the standard **properties** **UserName** and **Password** to ... **InteractionSpec** is used to define the function to invoke on the ...
www.ociweb.com/jnb/jnbMay2002.html - 31k - [Cached](#) - [Similar pages](#)

[Application Integration with Legacy Systems Using Java Connector ...](#)

InteractionSpec* **ConnectionSpec*** (Other metadata interfaces) ... The application server maintains a candidate **set** of **ManagedConnection** instances that it ...
developers.sun.com/sw/building/codesamples/integration_jca.html - 44k - [Cached](#) - [Similar pages](#)

[Chapter 21. JCA CCI](#)

If the adapter's **connectionSpec** **property** is specified, the adapter uses the **getConnection** ... **Record execute(InteractionSpec, RecordCreator)**, not **set** ...
www.springframework.org/docs/reference/cci.html - 55k - [Cached](#) - [Similar pages](#)

[Chapter 20. JCA CCI](#)

Some of the **ConnectionSpec** **properties** can often be configured in the application server (in ... **Record execute(InteractionSpec, RecordCreator)**, not **set** ...)
static.springframework.org/spring/docs/1.2.x/reference/cci.html - 52k - [Cached](#) - [Similar pages](#)

[WebSphere Adapter for Flat Files](#)

Overview: Deployment Overview: Deployment **Resource Adapter Custom Properties** to **set** **J2C Activation Specification** Select message listener, custom **properties** ...
publib.boulder.ibm.com/.../topic/com.ibm.iea.wpi_v6/
wa/6.0/FlatFile/WPSWIDv6_AdapterFlatFile/player.html - 28k - [Cached](#) - [Similar pages](#)

[Overview](#)

All adapters are strongly encouraged to use this **InteractionSpec** class. ... The **JCA properties** for the **Resource Adapter**, **Managed Connection Factory** for ...
publib.boulder.ibm.com/.../topic/com.ibm.iea.wa_v6/
wa/6.0.2/Overview/WPIv602_Adapter_Overview/player.html - 48k - [Cached](#) - [Similar pages](#)
[[More results from publib.boulder.ibm.com](#)]

[cci JCA CCI cci-introduction Introduction J2EE provides a ...](#)

If the adapter's **connectionSpec** **property** is specified, the adapter uses the ... center **Record execute(InteractionSpec, Record)** center not **set** center **Record** ...
fisheye1.cenqua.com/browse/~raw,r=1.6/springframework/spring/docs/reference/src/cci.xml
- 24k - [Cached](#) - [Similar pages](#)

[Exposing J2C interface properties - Patent 20050022205](#)

"**interactionSpec**" and "**connectionSpec**" are Java 2 Enterprise Edition **Java Connector Architecture** interfaces. Their **properties** are exposed as data in WSIF ...
www.freepatentsonline.com/20050022205.html - 37k - [Cached](#) - [Similar pages](#)

[\[PDF\] COPYRIGHTED MATERIAL](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)
set **property** methods for, 184. **IDL**, 579–580. of XML elements, 365–366 ...
ConnectionSpec interface, 744, 750. consistency of transactions, 687–688 ...

media.wiley.com/product_data/excerpt/55/07821414/0782141455-2.pdf - [Similar pages](#)

[PDF] [An Introduction to the J2EE Connector Architecture](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

properties required by **resource adapter** for message inflow ... constructor and add the connection to the associated **set**. – associateConnection should **set** ...

www.websphereusergroup.org.uk/downloads/05nov/Introduction%20to%20JCA.pdf -

[Similar pages](#)

Result Page: [1](#) [2](#) [3](#) [Next](#)

Download [Google Pack](#): free essential software for your PC

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2007 Google